



www.3c-sealants.co.uk

# 3C Sealants®



info@3c-sealants.co.uk



020 8524 1931



Unit 4, Chingford Industrial Centre, Hall Lane, London, E4 8DJ

## Product Technical Data Sheet

Product Name: *3C Sealants Tooling Spray*



### DESCRIPTION:

A ready to use sprayable tooling agent, used to help smooth all types of mastic sealants such as silicones, hybrid polymers and polyurethanes etc. It can be applied onto most common building substrates such as wood, ceramic, glass, plastic and much more.

### BENEFITS:

- Ready to use, no dilution needed
- Low odour
- Helps create a perfectly smooth finish
- Use for all types of mastic sealants
- Will not leave residues
- Can be used on internal and external surfaces
- For DIY and trade use
- Stops tooling sticks from sticking to wet material

### RECOMMENDED FOR:

- Specifically designed for finishing/tooling
- Spray on substrate or dip in smoothing tools
- Can be used on all types of sealants
- Applied on most common building substrates
- Can be used on natural stone (testing recommended prior to full application)

## PRODUCT INFORMATION

Packaging	750ml bottle
Shelf Life	12 months
Colour	Clear
Storage	Store in dry, cool conditions away from frost.
Dilution	Not required

### APPLICATION:

- Spray directly onto the sealant as soon as possible, before a skin begins to form.
- Do not apply with a brush, as this may leave marks in the sealant. Instead, dip smoothing tools into the Tooling Spray.
- Tool off as required using suitable smoothing tools.
- Supplied in the correct formulation for optimal tooling; no dilution or addition of water is required.

### HEALTH & SAFETY:

Keep out of reach of children. Contains 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction. Safety data sheet available on request.